19/05/2026

TECHNICAL DATASHEET

Code	D-Box-10
Brief Description	UN 4D/4DV Plywood box D-Box-10, mm 400x300x260h inner useful
Type	D-Box-10
Print	Neutral
Provided	Flat - without vermiculite
Approval	4D/X27.8/S and 4DV/X18.2/S
In compliance with	ISPM15
Country of origin	Italy
Tare (box weight)	4,32 kg
Dimensions outer	420 x 320 x 323 h mm
Dimensions inner	400 x 300 x 260 h mm



For shipping:

✔ ADR ✔ RID ✔ ADN ✔ IMDG ✔ IATA

Approved for	Max gross weight inner packaging kg	Max gross weight packaging kg	Certification / (Extension)	Minimum distance of Vermiculite between containers, bottom and lid walls mm	Closing
Nr. 6 glass bottles of 0,5 L each		27,80 (X27.80)	D-Box-10 – 4D/X27.8		Don't require nails or straps
Solid products contained in a plastic bag		27,80 (X27.80)	D-Box-10 – 4D/X27.8		Don't require nails or straps
Objects and inner packagings of all types	9,60	18,20 (X18.20)	D-Box-10 – 4DV/X18.2	46	Don't require nails or straps
Lithium Battery with Vermiculite (P908, P909, P910)	9,60	18,20 (X18.20)	4D/X27.8/S and 4DV/X18.2/S		—

Description

UN certified 4D and 4DV packagings (plywood boxes) suitable for the shipment of different objects and inner packagings as specified in the summary table. UN certified 4D plywood boxes can only be utilized with the specific packagings with which they have been tested. For the correct use of UN certified 4DV boxes it is necessary to follow the assembly instructions printed on every box. The correct preparation of these 4DV boxes provide that they be used in combination with one containment bag and Vermiculite (absorbent inert material).

SERPAC s.r.l. Via Campania, 4/6 20054 Segrate (MI)
dati fiscali P. IVA. 05083510965 cap. soc. € 20.000,00
reg. imprese Registro di Milano R.E.A.1795952
fatturazione cod. SDI. M5UXCR1 serpacsrl@lamiapec.it
contatti tel. (+39) 02 218 71 585 fax (+39) 02 269 52 031
web www.serpac.it info@serpac.it
azienda certificata UNI EN ISO 9001:2015 CERTIQUALITY n. 17284